

# Product datasheet

## Captair 483

Ductless filtering fume hood

### Safer to operate

- Erlab's advanced carbon filtration technology and/or HEPA/ULPA accommodates your specific needs
- Meets AFNOR NF X 15 211/ANSI Z9.5-2012 filtration efficiency standard (class 1 and 2)
- Sensors that detect filter breakthrough of solvents, acids or formaldehyde
- Safety back up filter in case of main filter saturation
- Continuous monitoring of Air face velocity
- Erlab Safety Program: application analysis and validation, usage certification, filter change reminders

### Simpler to use

With Smart Technology, you can easily see that the hood is operating safely. Should the light pulse you are notified that:

- Containment has been compromised or,
- The filter has breakthrough or,
- There is a Fan failure

### Flexibility

- The configurable filtration column will accommodate application changes
- No ductwork needed. This allows you to move the hood anywhere.

### Savings

- No ductwork cost
- Annual energy costs decreases significantly
- Energy savings outweigh filter replacement costs.

### Environment

- No dangerous chemical released into the atmosphere
- Low energy consumption





You get the highest level of filtration performance.



Smart Technology guided communication.






Heights according to the filtration column configuration


Type 1C or 1P	52 3/4"	Please add 5 3/4" between the last filter and the ceiling to allow a good air recirculation and to replace filters easily
Type 2C or 1P1C or 1C1P	56 1/2"	
Type 1P2C or 1P1C1P	59 5/8"	

**Work surfaces with built in spill tray**


**Tempered glass. Retention volume (8L)**




**TRESPA® TOPLAB<sup>PLUS</sup> Retention volume (7L)**



**304 L stainless steel. Retention volume (18L)**










**Benchcap: fixed work bench**





Designed with you in mind:  
Our filtration column can be  
configured for your specific  
application requirements.

		Liquid chemicals handlings	Powders handlings	Liquid chemicals and powders handlings	Liquid chemicals handlings in clean room
Customized filtration column	Class 1 according to the NF X 15-211		NA		
	Class 2 according to the NF X 15-211				

#### Available filters :

**C**

##### Carbon filtration for gases and vapours

AS:For organic vapours  
BE+:Polyvalent for acid + organic vapours  
F:For formaldehyde vapours  
K:For ammonia vapours

**P**

##### Particulate filtration for powders

HEPA H14:99.995 % efficiency filtration of particles over 0.1 µm in size  
ULPA U17:99.999995 % efficiency filtration of particles over 0.1 µm in size

 Ventilation

- **Molecode**  
Automatic alarm to detect a filtration fault

<b>Safety Standards</b>	AFNOR NF X 15-211:2009: France - BS 7989: England DIN 12 927:Germany - EN 1822:1998 (HEPA H14 & ULPA U17 Filters) - CE Marking
<b>Air Flow</b>	660 m3/h - 388 CFM
<b>Air Face Velocity</b>	0.4 to 0.6 m/s - 79 fpm to 118 fpm
<b>Voltage/Frequency</b>	90-220 V / 50-60 Hz
<b>Power consumption</b>	160 W
<b>Sash openings</b>	<a href="#">reverso sash</a>
<b>Structure</b>	Corrosion resistant electro-galvanized steel coated with anti-acid polymer
<b>Side and front panels</b>	Chemical resistant acrylic
<b>Filtration module</b>	Polypropylene

## Equipment

<b>Communication interface</b>	Simple communication by audible and light pulses: air face velocity, automatic alarm to detect a filtration fault, fan failure alarm
<b>Filtration technology</b>	3 columns that can be configured to handle liquids, powders, or both
<b>Carbon filtration for gases and vapors</b>	Following filtration column configuration (see table above)
<b>Particulate filtration for powders</b>	Following filtration column configuration (see table above)
<b>Internal lighting</b>	LED lighting > 650 Lux
<b>Anemometer</b>	Air face velocity alarm
<b>Chemical Listing</b>	List of approved chemicals

## Accessories

<b>Work Surfaces</b>	Tempered glass / TRESPA® TOPLAB <sup>PLUS</sup> / 304 L stainless steel
<b>Molecode</b>	Detection sensor for : Type S, for solvents / Type A, for acids / Type F, for formaldehydes
<b>Benches</b>	Fixed (Benchcap)
<b>Particulate Pre-filter</b>	Protects the main filter(s) from dust
<b>Transparent Back Panel</b>	Clear acrylic panel for easy viewing



# About Erlab

The Erlab Research and Development laboratory

Since 1968, **Erlab** has been a specialist, inventor and world leader in **ductless, zero-emission filtering fume hoods for laboratories** to provide total safety in chemical handling.

## 1 Erlab filtration

We provide technologies to protect laboratory staff from inhaling chemicals. This is made possible thanks to our Research and Development (R&D) department, which has continuously improved our filtration technology for more than 50 years. That's why, in 2009, we invented the ERLAB ABOVE label for tried and tested filtration technology.

## 2 The AFNOR NF X 15-211: 2009 standard

Erlab's filtration technology conforms to the NF X 15-211: 2009 standard, the industry's most demanding standard for molecular filtration, developed by a committee of independent scientists and specialized manufacturers.

This text imposes performance criteria linked to:

- Filtration efficiency
- Containment efficiency
- Air face velocity
- Documentation: chemical listing

## 3 The ESP program

A set of three services included with the purchase of each device designed to ensure your safety.



**eValQuest** Risk analysis – Determination of protection needs – Determination of ergonomic needs.



**ValPass** Certified installation – Total safety for handling.



**ValiGuard** Ongoing monitoring – Preventative and maintenance inspections – Device reconfiguration based on protection needs – Development of handling.

## 4 Flex technology

The combination of molecular and particulate filtration technologies allows a single device to meet laboratories' protection needs. This innovation from Erlab's R&D department offers unprecedented flexibility, versatility and value. A single device can be reconfigured over time and easily reassigned to other applications.

## 5 Smart technology

Smart technology is a simple and innovative means of communication that improves safety. This technology uses a light and sound signal to indicate the user's level of protection. The advantages of the technology are:

- 1/ Light pulsation: Real-time communication via LED light pulses intuitively alerts the user to the device's operating status.
- 2/ Simplicity: One-touch activation.
- 3/ Detection system: The exclusive detection system continuously monitors filtration performance.
- 4/ Built-in monitoring: This service provides direct access to the status, settings and history of your device.

France  
+33 (0) 2 32 09 55 80 | ventes@erlab.net

Germany  
0800 330 47 31 | export.north@erlab.net

United States  
+1 800-964-4434 | info@erlab.com

United Kingdom  
+44 (0) 1722 341 940 | export.north@erlab.net

China  
+86 (0) 512 5781 4085 | sales.china@erlab.com.cn

Italy  
+39 (0) 2 89 00 771 | export.south@erlab.net

Spain  
+34 936 732 474 | export.south@erlab.net

 **erlab** [usa.erlab.com](http://usa.erlab.com)  
You can breathe. [iaq.erlab.com](http://iaq.erlab.com)