




Captair Bio Smart

Mobile ductless filtering PCR workstation

Complete protection for RNA/DNA amplification



Captair Bio Smart

Mobile ductless filtering PCR workstation

SMART TECHNOLOGY

Simple, intuitive communication by light shows the status of the workstation

High efficiency particulate filtration

Internal UV light

Air flow monitoring

Internal LED lighting

UV resistant front and side panels


Ergonomic design

Easy to clean

Mobile or fixed benches



Download the eGuard App for remote control and monitoring



Life in the laboratory becomes simpler and safer

Specifications

320*



321



391



Model	320*	321	391		
Safety standards	NF EN 61010 - CE Marking	NF EN 61010 - CE Marking - EN 1822:1998 (HEPA H14 & ULPA U16 Filters)			
External width (mm-in)	825 / 32.4	810 / 31.8	1013 / 39.9		
External depth (mm-in)	630 / 24.8	670 / 26.4	670 / 26.4		
External height min-max (mm-in)	647 / 25.5	965-1059 / 37.9 - 41.7	965-1059 / 37.9 - 41.7		
Internal width (mm-in)	765 / 30.1	765 / 30.1	969 / 38.1		
Internal depth min-max (mm-in)	461-585 / 18.1 - 23	497-585 / 19.5 - 23	497-585 / 19.5 - 23		
Internal height (mm-in)	400 / 15.7	461 / 18.1	467 / 18.3		
Voltage / Frequency (V-Hz)	220-240 / 50-60 or 100-110 / 60	100-240 / 50-60			
Air flow (m³/h-CFM)	-	1P	1C1P	1P	1C1P
		200 / 118	245 / 144	200 / 118	245 / 144
Power consumption (Watts)	25	40	45	40	55
Decibel level (dBA)	< 40	54	57	55	57
Side and front panels	10 mm thick synthetic glass is designed to protect users from harmful UV rays and β (Bêta) emitted from radioactive isotopes such as: T(3H), 14C, 32P				
Structure	Corrosion resistant electro-galvanized steel coated with anti-acid polymer				
Filtration module	Polypropylene				

Filtration

Model	320*	321	391
Particulate filter (1P)	-	HEPA H14: This filtration technology traps particles larger than 0.1 µm with 99.995% efficiency according to the MPPS method set forth in the EN 1822-1 standard. ULPA U16: This filtration technology traps particles larger than 0.1 µm with 99.9995% efficiency according to the MPPS method set forth in the EN 1822-1 standard.	
Carbon filter (optional) (1C)	-	Adding a carbon filter to your enclosure allows protection of your samples from VOCs. AS filter : For organic vapors	
Particulate pre-filter	-	Protects particulate filters from dust in the laboratory environment (only for 1P version)	

Features

Model	320*	321	391
Worktop	Stainless steel 304 L / TRESPA® TopLab PLUS		
Bactericidal UV Lights	15W - Wavelength : 254 nm		
	0.08 mJ/ s/cm ²	0.08 mJ/ s/cm ²	0.13 mJ/ s/cm ²
Internal lighting	Compact fluorescent lighting - 18 Watts - IP 67	LED - IP 44-6000K	
	500 Lux	900 lux	950 lux
eGuard app (Android or iOS)	Mobile app for real time remote control of Smart devices		
Connectivity	-	RJ45 cable connection to view and change workstation settings (cable included)	
Anemometer	Monitors a drop in pressure that indicates pre-filter or filter replacement is required		

Accessories

Model	320*	321	391
Benches	Rolling cart (Mobicap) or fixed bench (Benchcap)		
Molecode S	-	Automatic detection of VOC filter breakthrough	

*Bio 320 is not a ductless or filtering unit

France
+33 (0) 2 32 09 55 80 | ventes@erlab.net

United States
+1 800-964-4434 | captainsales@erlab.com

China
+86 (0) 512 5781 4085 | sales.china@erlab.com.cn

Malaysia
(+603) 6419 4514 | erlab@tm.net.my

Germany
0800 330 47 31 | verkauf@erlab.net


United Kingdom
+44 (0) 1722 341 940 | salesuk@erlab.net

Italy
+39 (0) 2 89 00 771 | vendite@erlab.net

Spain
+34 936 732 474 | ventas@erlab.net

Protect your samples from contamination

Captair Bio Smart PCR Workstations are designed to protect sensitive biological applications against both environmental pollution and cross-contamination. They feature a high efficiency filtration system that provides a particle-free workstation around the manipulation. High energy UV light is used to decontaminate the worktop from biological cross-contamination between two operations.



Particulate free workstation*

- Protection against external contamination
- Internal air quality achieved by high efficiency particulate filter(s) (HEPA H14 / ULPA U16)
- Carbon filter (optional) to protect handlings from VOCs present in the laboratory atmosphere



UV decontamination

- Protect your samples from cross-contamination
- Powerful UV decontamination (254 nm lamp power)
- Adjustable timer
- Automatic UV lamp off switch in case the sash is opened when the UV light is on



Easy to clean

- Work surface is easy to clean
- Seamless worktop with smooth corners (available in TRESPA®TopLab PLUS or Stainless steel (304L))
- Low porosity material



Ergonomic design

- 3 models available for your handlings with large openings for easy access to your work.
- Slanted sash provides an ergonomic position for comfort and productivity
- High luminosity, internal LED lighting (daylight, light intensity > 800 lux)

Simpler to use*

- SMART Technology informs users about their protection using light and sound.
- Light and sound pulses provide real time information indicating that:



- The sash is open when the UV light is on.
- Air face velocity is compromised: check sash, pre-filter or HEPA / ULPA filter.
- Fan failure has occurred.

- **The eGuard App** provides remote control to monitor the workstation, change the settings, and delivers safety alerts immediately to your mobile, tablet or PC device.

Safer to operate*

- ULPA U16 filters guarantee 99.99995% filtration efficiency for particles larger than 0.1µm.
- HEPA H14 filters guarantee 99.995% filtration efficiency for particles larger than 0.1µm.
- Add a molecular filter for additional protection from fumes and vapors present in the laboratory air.
- The anemometer monitors a drop in pressure indicating that pre-filter or filter replacement is required.

*Available on Bio 321 and 391